



### SPECIFICATIONS

Floor Covering Type	EN 649	Heterogeneous PVC
Overall Thickness	EN 428	2.0 mm
Wear Layer Thickness	EN 429	0.3 mm
Wear Group	EN 660-1	Group T
Classification	EN 685	Residential: Class 23 Commercial: Class 31
Dimensional Stability	EN 434	≤ 0.25%
Behaviour to Fire	EN 13501	B <sub>f1</sub> -S <sub>1</sub>
Mekel Burner Test	Pass	
Underfloor Heating		Suitable to 27°C
Slip Resistance	EN 138903	R9
Residual Indentation	EN 433	≤ 0.10 mm
Castor Chair Suitability	EN 425	Yes
Colour Fastness	ISO 105-B02	≥ Grade 6
Chemical Resistance	EN 423	Excellent

### PRODUCT DIMENSIONS

Overall Thickness	EN 428	2.0 mm
Plank Length & Width	EN 427	177.8 x 1219.2 mm
Per Box: Quantity Sq. Meters	22/box	4.77 m <sup>2</sup>
Weight	EN 430	14.85 kg
Tile Length & Width	EN 427	314.0 x 625.0 mm
Per Box: Quantity & Sq. Meters	27/box	5.30 m <sup>2</sup>
Weight	EN 430	16.75 kg



Easy to clean  
and maintain



Suitable for all  
rooms



Warm and quiet  
underfoot



LVT with  
embossed surface

[www.adorefloors.com](http://www.adorefloors.com)

Adore UK • Gorse Lane • Coleshill • Birmingham B46 1JU  
T. +44 (0) 1675 433 075 • F. +44 (0) 1675 433 521

# adore<sup>®</sup>style



Adore Style... classic beauty, flawless performance.

adore<sup>®</sup>style WOOD COLLECTION



AS-1201



AS-1202



AS-1203



AS-1204



AS-1205



AS-1206



AS-1207



AS-1208



AS-1209



AS-1210



# adore style TILE COLLECTION



AS-1251



AS-1252



AS-1253



AS-1254



AS-1255

## Perfect style for your home

The natural elegance of Adore Style brings true-to-life design together with advanced performance for an enduring and flawless finish to your home.

Engineered with Nano-Silver™ and Micro-Cermic™ technology, Adore Style provides superior durability, longer wear and antibacterial and antimicrobial defence.

An environmentally responsible product, Adore Style is manufactured using more than 67% recycled material and is 100% recyclable.

Adore Style ... classic beauty, flawless performance.

