




TALIS 3

WALL MOUNTED LUMINAIRES / AUFPUTZLEUCHTEN, WANDLEUCHTEN




External housing color (.XX) / Externe Gehäusefarbe (.XX)

-  White (.01) / Weiß (.01)
-  Grey RAL 9006 (.02) / Grau RAL 9006 (.02)
-  Black RAL 9005 (.03) / Schwarz RAL 9005 (.03)

IP rating/ Schutzgrad: IP44

.XX | Fixture colour – e.g. 01
Farbe der Leuchte – z.B. 01


.YYY | LED type, standard: 830; 840; 930; 940;
Typ der LED: 830; 840; 930; 940;



TALIS 3

30.0301.XX.YYY	LED	1750lm	20W	CRI>90	MEDIUM - 23°
30.0302.XX.YYY	LED	1750lm	20W	CRI>90	FLOOD - 35°
30.0303.XX.YYY	LED	1750lm	20W	CRI>90	WIDE FLOOD - 58°
30.0311.XX.YYY	LED	2550lm	30W	CRI>90	MEDIUM - 23°
30.0312.XX.YYY	LED	2550lm	30W	CRI>90	FLOOD - 35°
30.0313.XX.YYY	LED	2550lm	30W	CRI>90	WIDE FLOOD - 58°

CRI > 80: 20W - 2000lm; 30W - 2900lm



TALIS 3 DALI

30.0321.XX.YYY	LED	1750lm	13W	CRI>90	MEDIUM - 23°
30.0322.XX.YYY	LED	1750lm	13W	CRI>90	FLOOD - 35°
30.0323.XX.YYY	LED	1750lm	13W	CRI>90	WIDE FLOOD - 58°
30.0331.XX.YYY	LED	2550lm	20W	CRI>90	MEDIUM - 23°
30.0332.XX.YYY	LED	2550lm	20W	CRI>90	FLOOD - 35°
30.0333.XX.YYY	LED	2550lm	20W	CRI>90	WIDE FLOOD - 58°